

GTW-03

138 x 64 x 31 mm

For IoT
communication**Main Features**

- WiFi: IEEE 802.11 b/g/n
- 10/100 Ethernet interface (optional)
- USB Type A
- RS485
- Power supply: 10 to 30 Vdc, 200mA

Applications

Air conditioners, heating systems, commercial and professional refrigerators, blast chillers and freezers, dough-retard provers, heating/cooling combi catering machines, professional ovens, ice makers, transport refrigeration, high-end domestic refrigerators.

■ The GTW-03 Gateway is a computer with Real Time Operating System, memory and communication ports, designed specifically to run IoT communication securely.

■ Easy-to-install: connects the GTW-03 to the Modbus port of the LAE controller, which is recognised automatically.

■ Easy-to-configure: via a Smartphone or PC, connect to the web page of the GTW-03 and connect it to your WiFi Access Point or to your cabled network.

■ It may be customised: the GTW-03 automatically connects to the LAE Cloud designed in cooperation with Servitly. In addition, with a few simple adaptations, it's possible to send data to any IoT service provider (please get in touch with our local distributor to get a detailed offer).

Technical Data

CPU	STM32
Core	Cortex-M4 @168MHz
Memory	4MB NOR FLASH
OS	Segger RTOS
Power supply	10 to 26 Vdc, 150mA
Tiny Size	138 x 64 x 31 mm
Internal web server for configuration and diagnosis	